

## ► SPREADERS

### SPREADERS TYPE BY SECTION AND PROFILE REFERENCE

2004

	Spreader 1	Spreader 2	Spreader 3
<b>F35</b>	BF2	BF2	
<b>F50</b>	BF2	BF2	
<b>F67</b>	BF2	BF2	
<b>F101</b>	BF2	BF2	
<b>I137</b>	BF2	BF2	
<b>I180</b>	BF3	BF3	
<b>I260</b>	BF3	BF3	BF3
<b>I330</b>	BF3	BF3	BF3
<b>NG51</b>	BF3	BF3	BF3
<b>NG60</b>	BF4	BF3	BF3
<b>NG70</b>	BF4	BF4	BF3
<b>NG80</b>	BF5	BF4	BF4
<b>NG86</b>	BF5	BF4	BF4
<b>NG105</b>	BF5	BF5	BF4

#### ANODIZED SPREADER SECTION






	Réf. / Ref.
BF2	21000026003
BF3	21000036003
BF4	21000046003
BF5	21000056003
BF6	21000066003

Sections available in 6 meters maximum length.

## ► SPREADERS SECTIONS

Our standard spreaders are clear, anodized, tapered and manufactured to length cut at angled from 0 to 30 degrees.



Sections	Inertias	XX'		Dimensions (mm)	Weight kg/m	Standard length (m)
			YY'			
<b>BF 2</b> 		6	1,1	19 x 55	0,7	6
<b>BF 3</b> 		27,2	5,9	30 x 74	1,2	6
<b>BF 4</b> 		63	7,7	35 x 105	1,8	6
<b>BF 5</b> 		209	18,9	44 x 154,5	2,8	6
<b>BF 6</b> 		362	39,4	53 x 167	3,4	6