

## ► VANG FITTING



37560230305

2004

CODE	Size	Length open	Length closed	Course mm	Max spring strength	Mast attachment	Boom attachment	Pin on mast	Pin on boom
37560200005	0	1350	1160	190	0	3521181PF05	35243200164	8	10
37560210105	1	1160	970	190	100	3521181PF15	35243200164	14	14
37560220105	2	1395	1155	240	115	3521181PF15	35243202734/6504	14	14
37560230105	3	1740	1450	290	115	3521181PF15	35243202734/6504	14	14
37560240105	4	2000	1710	290	115	3521181PF15/PF25	35243202734/6504	14	14
37560230205	3	1740	1450	290	230	3521181PF15/PF25	35243202734/6504	14	14
37560240205	4	2000	1710	290	230	3521181PF15/PF25	35243202734/6504	14	14
37560250305	5	2000	1710	290	345	3521181PF25	35243206504	14	14
37560250405	5	2000	1710	290	460	3521181PF25	35243206504	14	14
37560250505	5	2000	1710	290	575	3521181PF25	35243206504	14	14
37560250605	5	2300	2010	290	345	3521181PF25	35243206504	14	14
37560250705	5	2300	2010	290	460	3521181PF25	35243206504	14	14
37560250805	5	2300	2010	290	575	3521181PF25	35243206504	14	14

Purchase and bridle not included.

### Bridle

Réf.		Size					
		0	1	2	3	4	5
43505061600	Lg 1,6 m	X	X	X			
43505062000	Lg 2 m				X		
43505062200	Lg 2,2 m					X	*

\* On request.

Boom	Rigid vang attachment	Width	Thickness
<b>F36</b>	35243200164	23 mm	1,5 mm
<b>F60</b>	35243200164		
<b>F125</b>	35243202734	26,5 mm	2,5 mm
<b>F220</b>	35243202734		
<b>F550</b>	35243206504	30 mm	4 mm
<b>F810</b>	35243206504		
<b>F1700</b>	35243206504		
<b>F3400</b>	35243206504		